

Belief revision-based case-based reasoning

Julien Cojan¹ and Jean Lieber²³⁴

¹ INRIA Sophia-Antipolis, Edelweiss Project, julien.cojan@inria.fr

² Université de Lorraine, LORIA, UMR 7503 — Vandœuvre-lès-Nancy, F-54506, France, jean.lieber@loria.fr

³ CNRS, LORIA, UMR 7503 — Vandœuvre-lès-Nancy, F-54506, France

⁴ Inria — Villers-lès-Nancy, F-54602, France

Remark on the difference between the paper and the talk

The paper gathers several results on revision-based CBR and is rather technical


Remark on the difference between the paper and the talk

The paper gathers several results on revision-based CBR and is rather technical

The talk will make some simplifying assumptions and will try to be more intuitive

Outline of the talk

preliminaries



Preliminaries

Formalism

- ▶ Generalisation from propositional logic with n variables:
 - ▶ $\mathcal{U} = \{\text{false}, \text{true}\}^n$: set of the interpretations
 - ▶ A formula φ represents a subset $\text{Mod}(\varphi)$ of \mathcal{U}

Formalism

- ▶ Generalisation from propositional logic with n variables:
 - ▶ $\mathcal{U} = \{\text{false}, \text{true}\}^n$: set of the interpretations
 - ▶ A formula φ represents a subset $\text{Mod}(\varphi)$ of \mathcal{U}
- ▶ Generalisation:
 - ▶ \mathcal{U} : a given set (“the universe of instances/interpretations”)
 - ▶ \mathcal{L} : the representation language
 - ▶ Semantics: $\varphi \in \mathcal{L} \mapsto \text{Mod}(\varphi) \in 2^{\mathcal{U}}$
 - ▶ With $A = \text{Mod}(\varphi)$ and $B = \text{Mod}(\chi)$
 - ▶ $\varphi \models \chi$ if $A \subseteq B$
 - ▶ φ is satisfiable if $A \neq \emptyset$

Distance

- ▶ $d : \mathcal{U} \times \mathcal{U} \rightarrow [0; +\infty]$ is a distance if

$$d(x, y) = 0 \quad \text{iff} \quad x = y$$

(no other condition required in this talk)

Belief Revision

Belief revision (introduction)

- ▶ Belief base = knowledge base (no difference in this talk)

Belief revision (introduction)

- ▶ Belief base = knowledge base (no difference in this talk)
- ▶ Given
 - ▶ ψ a revisable consistent knowledge base
 - ▶ μ a non revisable consistent knowledge base

Belief revision (introduction)

- ▶ Belief base = knowledge base (no difference in this talk)
- ▶ Given
 - ▶ ψ a revisable consistent knowledge base
 - ▶ μ a non revisable consistent knowledge base
- ▶ A revision $\boxed{\psi \dot{+} \mu}$ of ψ by μ is a knowledge base obtained by *minimal* modification of ψ so that it is consistent with μ :
 - ▶ $\psi \mapsto \psi'$
 - ▶ $\psi \dot{+} \mu = \psi' \cap \mu$

Belief revision (introduction)

- ▶ Belief base = knowledge base (no difference in this talk)
- ▶ Given
 - ▶ ψ a revisable consistent knowledge base
 - ▶ μ a non revisable consistent knowledge base
- ▶ A revision $\boxed{\psi \dot{+} \mu}$ of ψ by μ is a knowledge base obtained by *minimal* modification of ψ so that it is consistent with μ :
 - ▶ $\psi \mapsto \psi'$
 - ▶ $\psi \dot{+} \mu = \psi' \cap \mu$
- ▶ Different ways to model *minimal modification*
hence different revision operators

Belief revision (introduction)

- ▶ Belief base = knowledge base (no difference in this talk)
- ▶ Given
 - ▶ ψ a revisable consistent knowledge base
 - ▶ μ a non revisable consistent knowledge base
- ▶ A revision $\boxed{\psi \dot{+} \mu}$ of ψ by μ is a knowledge base obtained by *minimal* modification of ψ so that it is consistent with μ :
 - ▶ $\psi \mapsto \psi'$
 - ▶ $\psi \dot{+} \mu = \psi' \cap \mu$
- ▶ Different ways to model *minimal modification* hence different revision operators
- ▶ In the following, $\dot{+}$ is defined on $\mathcal{L} \times \mathcal{L}$ or on $2^{\mathcal{U}} \times 2^{\mathcal{U}}$:

$$\text{Mod}(\psi \dot{+} \mu) = \text{Mod}(\psi) \dot{+} \text{Mod}(\mu)$$

Belief revision (postulates)

- ▶ AGM postulates (1985)

Belief revision (postulates)

- ▶ AGM postulates (1985)
- ▶ Katsuno & Mendelzon (1992):
reformulation in propositional logic


Belief revision (postulates)

- ▶ AGM postulates (1985)
- ▶ Katsuno & Mendelzon (1992):
reformulation in propositional logic
- ▶ Easy to generalise in our formalism (see further)

Belief revision (distance-based revision operators)

With d , a distance on \mathcal{U} , $A \subseteq \mathcal{U}$, $B \subseteq \mathcal{U}$:


$$A \dot{+}^d B = \{b \in B \mid d(A, b) = d(A, B)\}$$



Belief revision (distance-based revision operators)

With d , a distance on \mathcal{U} , $A \subseteq \mathcal{U}$, $B \subseteq \mathcal{U}$:


$$A \dot{+}^d B = \{b \in B \mid d(A, b) = d(A, B)\}$$



Belief revision (distance-based revision operators)

With d , a distance on \mathcal{U} , $A \subseteq \mathcal{U}$, $B \subseteq \mathcal{U}$:


$$A \dot{+}^d B = \{b \in B \mid d(A, b) = d(A, B)\}$$



Belief revision (distance-based revision operators)

With d , a distance on \mathcal{U} , $A \subseteq \mathcal{U}$, $B \subseteq \mathcal{U}$:

$$A \dot{+}^d B = \{b \in B \mid d(A, b) = d(A, B)\}$$



Case-Based Reasoning

CBR: problems, solutions and cases

Assumption for the talk: problem-solution decomposition of cases

CBR: problems, solutions and cases

Assumption for the talk: problem-solution decomposition of cases

- ▶ A problem instance x : an element of \mathcal{U}_{pb}

CBR: problems, solutions and cases

Assumption for the talk: problem-solution decomposition of cases

- ▶ A problem instance x : an element of \mathcal{U}_{pb}
- ▶ A problem pb : a class of problem instances, $pb \in 2^{\mathcal{U}_{pb}}$

CBR: problems, solutions and cases

Assumption for the talk: problem-solution decomposition of cases

- ▶ A problem instance x : an element of \mathcal{U}_{pb}
- ▶ A problem pb : a class of problem instances, $pb \in 2^{\mathcal{U}_{pb}}$
- ▶ A solution instance y : an element of \mathcal{U}_{sol}

CBR: problems, solutions and cases

Assumption for the talk: problem-solution decomposition of cases

- ▶ A problem instance x : an element of \mathcal{U}_{pb}
- ▶ A problem pb : a class of problem instances, $pb \in 2^{\mathcal{U}_{pb}}$
- ▶ A solution instance y : an element of \mathcal{U}_{sol}
- ▶ A solution sol : a class of solution instances, $sol \in 2^{\mathcal{U}_{sol}}$

CBR: problems, solutions and cases

Assumption for the talk: problem-solution decomposition of cases

- ▶ A problem instance x : an element of \mathcal{U}_{pb}
- ▶ A problem pb : a class of problem instances, $pb \in 2^{\mathcal{U}_{pb}}$
- ▶ A solution instance y : an element of \mathcal{U}_{sol}
- ▶ A solution sol : a class of solution instances, $sol \in 2^{\mathcal{U}_{sol}}$
- ▶ There exists a relation “ x has for solution y ” but it is incompletely known.

CBR: problems, solutions and cases

Assumption for the talk: problem-solution decomposition of cases

- ▶ A problem instance x : an element of \mathcal{U}_{pb}
- ▶ A problem pb : a class of problem instances, $pb \in 2^{\mathcal{U}_{pb}}$
- ▶ A solution instance y : an element of \mathcal{U}_{sol}
- ▶ A solution sol : a class of solution instances, $sol \in 2^{\mathcal{U}_{sol}}$
- ▶ There exists a relation “ x has for solution y ” but it is incompletely known.
- ▶ A case C is given by a problem pb and a solution $sol(pb)$ of pb : $C = pb \times sol(pb)$.

CBR: problems, solutions and cases

Assumption for the talk: problem-solution decomposition of cases

- ▶ A problem instance x : an element of \mathcal{U}_{pb}
- ▶ A problem pb : a class of problem instances, $pb \in 2^{\mathcal{U}_{pb}}$
- ▶ A solution instance y : an element of \mathcal{U}_{sol}
- ▶ A solution sol : a class of solution instances, $sol \in 2^{\mathcal{U}_{sol}}$
- ▶ There exists a relation “ x has for solution y ” but it is incompletely known.
- ▶ A case C is given by a problem pb and a solution $sol(pb)$ of pb : $C = pb \times sol(pb)$.
- ▶ Thus, $C \in 2^{\mathcal{U}}$ where $\mathcal{U} = \mathcal{U}_{pb} \times \mathcal{U}_{sol}$.

CBR (input/output)

Input

Output

CBR (input/output)

Input

- ▶ The target case $\text{Target} = \text{tgt} \times \mathcal{U}_{\text{sol}}$ (unknown solution)
(often $\text{tgt} = \{x^t\}$)

Output

CBR (input/output)

Input

- ▶ The target case $\text{Target} = \text{tgt} \times \mathcal{U}_{\text{sol}}$ (unknown solution)
(often $\text{tgt} = \{x^t\}$)
- ▶ The case base CaseBase : set of the cases available to the system: $\text{Source} \in \text{CaseBase}$, $\text{Source} = \text{srce} \times \text{sol}(\text{srce})$
(often $\text{Source} = \{(x^s, y^s)\}$)

Output

CBR (input/output)

Input

- ▶ The target case $\text{Target} = \text{tgt} \times \mathcal{U}_{\text{sol}}$ (unknown solution)
(often $\text{tgt} = \{x^t\}$)
- ▶ The case base CaseBase: set of the cases available to the system: $\text{Source} \in \text{CaseBase}$, $\text{Source} = \text{srce} \times \text{sol}(\text{srce})$
(often $\text{Source} = \{(x^s, y^s)\}$)
- ▶ The domain knowledge $\text{DK} \subseteq \mathcal{U}$
a necessary condition for a case instance $a = (x, y) \in \mathcal{U}$ to be licit
if $a \notin \text{DK}$ then a is not licit

Output

CBR (input/output)

Input

- ▶ The target case $\text{Target} = \text{tgt} \times \mathcal{U}_{\text{sol}}$ (unknown solution)
(often $\text{tgt} = \{x^t\}$)
- ▶ The case base CaseBase : set of the cases available to the system: $\text{Source} \in \text{CaseBase}$, $\text{Source} = \text{srce} \times \text{sol}(\text{srce})$
(often $\text{Source} = \{(x^s, y^s)\}$)
- ▶ The domain knowledge $\text{DK} \subseteq \mathcal{U}$
a necessary condition for a case instance $a = (x, y) \in \mathcal{U}$ to be licit
$$\text{if } a \notin \text{DK} \text{ then } a \text{ is not licit}$$
- ▶ Other knowledge containers (similarity, AK)

Output

CBR (input/output)

Input

- ▶ The target case $\text{Target} = \text{tgt} \times \mathcal{U}_{\text{sol}}$ (unknown solution)
(often $\text{tgt} = \{x^t\}$)
- ▶ The case base CaseBase : set of the cases available to the system: $\text{Source} \in \text{CaseBase}$, $\text{Source} = \text{srce} \times \text{sol}(\text{srce})$
(often $\text{Source} = \{(x^s, y^s)\}$)
- ▶ The domain knowledge $\text{DK} \subseteq \mathcal{U}$
a necessary condition for a case instance $a = (x, y) \in \mathcal{U}$ to be licit
$$\text{if } a \notin \text{DK} \text{ then } a \text{ is not licit}$$
- ▶ Other knowledge containers (similarity, AK)


Output

$\text{sol}(\text{tgt}) \in 2^{\mathcal{U}_{\text{sol}}}$ such that the hypothesis
“ $\text{sol}(\text{tgt})$ solves tgt ” is likely (...).
(often $\text{sol}(\text{tgt}) = \{y^t\}$)


CBR (retrieval and adaptation)

tgt


CBR (retrieval and adaptation)




CBR (retrieval and adaptation)



CBR (retrieval and adaptation)




CBR (retrieval and adaptation)





CBR (example)


<http://taaable.fr>


Fruit pie recipe
without apple?

















Revision-Based CBR

Revision-based adaptation (intuition)

- ▶ Adaptation: modification of $\text{srce} \times \text{sol}(\text{srce})$
so that it is consistent with $\text{tgt} \times \mathcal{U}_{\text{sol}}$

//

- ▶ Revision: modification of ψ
so that it is consistent with μ

Revision-based adaptation (definition)

$$\text{tgt} \times \text{sol}(\text{tgt}) = (\quad \text{srce} \times \text{sol}(\text{srce})) \quad (\quad \text{tgt} \times \mathcal{U}_{\text{sol}})$$

Revision-based adaptation (definition)

$$\text{tgt} \times \text{sol}(\text{tgt}) = (\text{DK} \cap \text{srce} \times \text{sol}(\text{srce})) \quad (\text{DK} \cap \text{tgt} \times \mathcal{U}_{\text{sol}})$$

Revision-based adaptation (definition)

$$\text{tgt} \times \text{sol}(\text{tgt}) = (\text{DK} \cap \text{srce} \times \text{sol}(\text{srce})) \dot{+} (\text{DK} \cap \text{tgt} \times \mathcal{U}_{\text{sol}})$$

Revision-based adaptation (definition)

$$\text{tgt} \times \text{sol}(\text{tgt}) = (\text{DK} \cap \text{srce} \times \text{sol}(\text{srce})) \dot{+}_{\text{AK}} (\text{DK} \cap \text{tgt} \times \mathcal{U}_{\text{sol}})$$

Revision-based adaptation (properties)

	revision postulates (reformulated)	$\dot{+}$ -adaptation properties
$\dot{+} 1$	$A \dot{+} B \subseteq B$	The result of the adaptation is consistent with DK.
$\dot{+} 2$	if $A \cap B \neq \emptyset$ then $A \dot{+} B = A \cap B$	If the target case is consistent with the source case then this latter is deductively reused for solving the target case.
$\dot{+} 3$	if $B \neq \emptyset$ then $A \dot{+} B \neq \emptyset$	Unless the target case is DK-inconsistent, the adaptation gives a consistent result.
$\dot{+} 4$ $\dot{+} 5$	if $(A \dot{+} B) \cap C \neq \emptyset$ then $A \dot{+} (B \cap C) = (A \dot{+} B) \cap C$	Adaptation by <i>minimal</i> modification (according to $\dot{+}$).
$\dot{+} 6$	The result of the revision is representable in \mathcal{L} .	The result of the adaptation is representable in \mathcal{L} .

Example 1: in prop. logic, with Dalal revision operator

Example 1: in prop. logic, with Dalal revision operator

- ▶ $\text{tgt} = \text{pie} \wedge \text{fruit} \wedge \neg \text{apple}$
(pie: recipe of pies, apple: recipes with apples, etc.)

Example 1: in prop. logic, with Dalal revision operator

- ▶ $\text{tgt} = \text{pie} \wedge \text{fruit} \wedge \neg \text{apple}$
(pie: recipe of pies, apple: recipes with apples, etc.)
- ▶ $\text{srce} = \text{pie} \wedge \text{apple}$
 $\text{sol}(\text{srce}) = \text{pie_shell} \wedge \text{sugar}$

Example 1: in prop. logic, with Dalal revision operator

- ▶ $\text{tgt} = \text{pie} \wedge \text{fruit} \wedge \neg \text{apple}$
(pie: recipe of pies, apple: recipes with apples, etc.)
- ▶ $\text{srce} = \text{pie} \wedge \text{apple}$
 $\text{sol}(\text{srce}) = \text{pie_shell} \wedge \text{sugar}$
- ▶ $\text{DK} = \left\{ \begin{array}{l} \text{apple} \vee \text{pear} \Leftrightarrow \text{pome_fruit}, \\ \text{pome_fruit} \Rightarrow \text{fruit}, \quad \text{etc.} \end{array} \right\}$

Example 1: in prop. logic, with Dalal revision operator

- ▶ $\text{tgt} = \text{pie} \wedge \text{fruit} \wedge \neg \text{apple}$
(pie: recipe of pies, apple: recipes with apples, etc.)
- ▶ $\text{srce} = \text{pie} \wedge \text{apple}$
 $\text{sol}(\text{srce}) = \text{pie_shell} \wedge \text{sugar}$
- ▶ $\text{DK} = \left\{ \begin{array}{l} \text{apple} \vee \text{pear} \Leftrightarrow \text{pome_fruit}, \\ \text{pome_fruit} \Rightarrow \text{fruit}, \quad \text{etc.} \end{array} \right\}$
- ▶ $\dot{+} = \text{Dalal revision operator} = \dot{+}^{d_H}$ with d_H : Hamming distance

$$\begin{aligned} d_H(\mathcal{I}, \mathcal{J}) &= \text{number of flips of variables from } \mathcal{I} \text{ to } \mathcal{J} \\ &= \text{card}(\{\text{variable } a \mid \mathcal{I}(a) \neq \mathcal{J}(a)\}) \end{aligned}$$

Example 1: in prop. logic, with Dalal revision operator

- ▶ $\text{tgt} = \text{pie} \wedge \text{fruit} \wedge \neg \text{apple}$
(pie: recipe of pies, apple: recipes with apples, etc.)
- ▶ $\text{srce} = \text{pie} \wedge \text{apple}$
 $\text{sol}(\text{srce}) = \text{pie_shell} \wedge \text{sugar}$
- ▶ $\text{DK} = \left\{ \begin{array}{l} \text{apple} \vee \text{pear} \Leftrightarrow \text{pome_fruit}, \\ \text{pome_fruit} \Rightarrow \text{fruit}, \quad \text{etc.} \end{array} \right\}$
- ▶ $\dot{+} = \text{Dalal revision operator} = \dot{+}^{d_H}$ with d_H : Hamming distance

$$\begin{aligned} d_H(\mathcal{I}, \mathcal{J}) &= \text{number of flips of variables from } \mathcal{I} \text{ to } \mathcal{J} \\ &= \text{card}(\{\text{variable } a \mid \mathcal{I}(a) \neq \mathcal{J}(a)\}) \end{aligned}$$

$$\text{tgt} \wedge \text{sol}(\text{tgt}) = \text{pie} \wedge \boxed{\text{pear}} \wedge \text{pie_shell} \wedge \text{sugar}$$

Example 2: in prop. logic, using adaptation rules

Example 2: in prop. logic, using adaptation rules

- ▶ Same `tgt`, `srce`, `sol(srce)` and DK

Example 2: in prop. logic, using adaptation rules

- ▶ Same **tgt**, **srce**, **sol(srce)** and DK
- ▶ Use of adaptation knowledge given by adaptation rules

$$AK = \left\{ \begin{array}{l} \text{salad} \wedge \text{vinegar} \rightsquigarrow \text{salad} \wedge \text{lemon} \wedge \text{salt}, \\ \text{apple} \rightsquigarrow \text{pear} \wedge \text{almond_powder}, \quad \text{etc.} \end{array} \right\}$$

Example 2: in prop. logic, using adaptation rules

- ▶ Same **tgt**, **srce**, **sol(srce)** and DK
- ▶ Use of adaptation knowledge given by adaptation rules

$$\text{AK} = \left\{ \begin{array}{l} \text{salad} \wedge \text{vinegar} \rightsquigarrow \text{salad} \wedge \text{lemon} \wedge \text{salt}, \\ \text{apple} \rightsquigarrow \text{pear} \wedge \text{almond_powder}, \quad \text{etc.} \end{array} \right\}$$

- ▶ $\dot{+} = \dot{+}^{d_{\text{AK}}}$ with d_{AK} defined by
 - ▶ Version 1:

$$d_{\text{AK}}(\mathcal{I}, \mathcal{J}) = \text{length of the shortest AK-path from } \mathcal{I} \text{ to } \mathcal{J}$$

Example 2: in prop. logic, using adaptation rules

- ▶ Same **tgt**, **srce**, **sol(srce)** and DK
- ▶ Use of adaptation knowledge given by adaptation rules

$$AK = \left\{ \begin{array}{l} \text{salad} \wedge \text{vinegar} \rightsquigarrow \text{salad} \wedge \text{lemon} \wedge \text{salt}, \\ \text{apple} \rightsquigarrow \text{pear} \wedge \text{almond_powder}, \quad \text{etc.} \end{array} \right\}$$

- ▶ $\dot{+} = \dot{+}^{d_{AK}}$ with d_{AK} defined by
 - ▶ Version 1:

$$d_{AK}(\mathcal{I}, \mathcal{J}) = \text{length of the shortest AK-path from } \mathcal{I} \text{ to } \mathcal{J}$$

Limitation: $d_{AK}(\mathcal{I}, \mathcal{J}) = +\infty$ if no AK-path from \mathcal{I} to \mathcal{J} exist

Example 2: in prop. logic, using adaptation rules

- ▶ Same **tgt**, **srce**, **sol(srce)** and DK
- ▶ Use of adaptation knowledge given by adaptation rules

$$AK = \left\{ \begin{array}{l} \text{salad} \wedge \text{vinegar} \rightsquigarrow \text{salad} \wedge \text{lemon} \wedge \text{salt}, \\ \text{apple} \rightsquigarrow \text{pear} \wedge \text{almond_powder}, \quad \text{etc.} \end{array} \right\}$$

- ▶ $\dot{+} = \dot{+}^{d_{AK}}$ with d_{AK} defined by

- ▶ Version 1:

$$d_{AK}(\mathcal{I}, \mathcal{J}) = \text{length of the shortest AK-path from } \mathcal{I} \text{ to } \mathcal{J}$$

Limitation: $d_{AK}(\mathcal{I}, \mathcal{J}) = +\infty$ if no AK-path from \mathcal{I} to \mathcal{J} exist

- ▶ Version 2:

$$d_{AK}(\mathcal{I}, \mathcal{J}) = \begin{array}{l} \text{length of the shortest path from } \mathcal{I} \text{ to } \mathcal{J} \\ \text{using adaptation rules and flips of variables} \end{array}$$

(when $AK = \emptyset$, $d_{AK} = d_H$)

Example 2: in prop. logic, using adaptation rules

- ▶ Same **tgt**, **srce**, **sol(srce)** and DK
- ▶ Use of adaptation knowledge given by adaptation rules

$$AK = \left\{ \begin{array}{l} \text{salad} \wedge \text{vinegar} \rightsquigarrow \text{salad} \wedge \text{lemon} \wedge \text{salt}, \\ \text{apple} \rightsquigarrow \text{pear} \wedge \text{almond_powder}, \quad \text{etc.} \end{array} \right\}$$

- ▶ $\dot{+} = \dot{+}^{d_{AK}}$ with d_{AK} defined by

- ▶ Version 1:

$$d_{AK}(\mathcal{I}, \mathcal{J}) = \text{length of the shortest AK-path from } \mathcal{I} \text{ to } \mathcal{J}$$

Limitation: $d_{AK}(\mathcal{I}, \mathcal{J}) = +\infty$ if no AK-path from \mathcal{I} to \mathcal{J} exist

- ▶ Version 2:

$$d_{AK}(\mathcal{I}, \mathcal{J}) = \begin{array}{l} \text{length of the shortest path from } \mathcal{I} \text{ to } \mathcal{J} \\ \text{using adaptation rules and flips of variables} \end{array}$$

(when $AK = \emptyset$, $d_{AK} = d_H$)

$$\text{tgt} \wedge \text{sol}(\text{tgt}) = \text{pie} \wedge \boxed{\text{pear} \wedge \text{almond_powder}} \wedge \text{pie_shell} \wedge \text{sugar}$$

Example 3: adaptation of quantities (1/2)

Example 3: adaptation of quantities (1/2)

- ▶ \mathcal{L} : conjunction of linear constraints
(on integers and real numbers)

Example 3: adaptation of quantities (1/2)

- ▶ \mathcal{L} : conjunction of linear constraints
(on integers and real numbers)
- ▶ $\text{tgt} = (\text{nb_apple} = 0)$

Example 3: adaptation of quantities (1/2)

- ▶ \mathcal{L} : conjunction of linear constraints
(on integers and real numbers)
- ▶ $\text{tgt} = (\text{nb_apple} = 0)$
- ▶ $\text{srce} \wedge \text{sol}(\text{srce}) = (\text{nb_pie_shell} = 1) \wedge (\text{nb_apple} = 6) \wedge$
 $(\text{mass_sugar} = 60) \wedge (\text{nb_pear} = 0) \wedge$
 $(\text{nb_tomato} = 0) \wedge \dots$

Example 3: adaptation of quantities (1/2)

- ▶ \mathcal{L} : conjunction of linear constraints
(on integers and real numbers)
- ▶ $\text{tgt} = (\text{nb_apple} = 0)$
- ▶ $\text{srce} \wedge \text{sol}(\text{srce}) = (\text{nb_pie_shell} = 1) \wedge (\text{nb_apple} = 6) \wedge$
 $(\text{mass_sugar} = 60) \wedge (\text{nb_pear} = 0) \wedge$
 $(\text{nb_tomato} = 0) \wedge \dots$
 $(\text{mass_apple} = 242 \times \text{nb_apple}) \wedge$
 $(\text{mass_pear} = 166 \times \text{nb_pear}) \wedge \dots$
- ▶ $\text{DK} = (\text{mass_fruit} = \text{mass_apple} + \text{mass_pear} + \dots) \wedge$
 $(\text{mass_carbohydrates} = \text{mass_sugar} + 33 \times \text{nb_apple}$
 $+ 26 \times \text{nb_pear} + \dots) \wedge \dots$

Example 3: adaptation of quantities (1/2)

- ▶ \mathcal{L} : conjunction of linear constraints
(on integers and real numbers)
- ▶ $\text{tgt} = (\text{nb_apple} = 0)$
- ▶ $\text{srce} \wedge \text{sol}(\text{srce}) = (\text{nb_pie_shell} = 1) \wedge (\text{nb_apple} = 6) \wedge$
 $(\text{mass_sugar} = 60) \wedge (\text{nb_pear} = 0) \wedge$
 $(\text{nb_tomato} = 0) \wedge \dots$
 $(\text{mass_apple} = 242 \times \text{nb_apple}) \wedge$
 $(\text{mass_pear} = 166 \times \text{nb_pear}) \wedge \dots$
- ▶ $\text{DK} = (\text{mass_fruit} = \text{mass_apple} + \text{mass_pear} + \dots) \wedge$
 $(\text{mass_carbohydrates} = \text{mass_sugar} + 33 \times \text{nb_apple}$
 $\quad + 26 \times \text{nb_pear} + \dots) \wedge \dots$
- ▶ $x = (x_1, x_2, \dots, x_n) \in \mathcal{U}, x_k \in \mathbb{R}_+ \text{ or } x_k \in \mathbb{N}$

Example 3: adaptation of quantities (1/2)

- ▶ \mathcal{L} : conjunction of linear constraints
(on integers and real numbers)
- ▶ $\text{tgt} = (\text{nb_apple} = 0)$
- ▶ $\text{srce} \wedge \text{sol}(\text{srce}) = (\text{nb_pie_shell} = 1) \wedge (\text{nb_apple} = 6) \wedge$
 $(\text{mass_sugar} = 60) \wedge (\text{nb_pear} = 0) \wedge$
 $(\text{nb_tomato} = 0) \wedge \dots$
 $(\text{mass_apple} = 242 \times \text{nb_apple}) \wedge$
 $(\text{mass_pear} = 166 \times \text{nb_pear}) \wedge \dots$
- ▶ $\text{DK} = (\text{mass_fruit} = \text{mass_apple} + \text{mass_pear} + \dots) \wedge$
 $(\text{mass_carbohydrates} = \text{mass_sugar} + 33 \times \text{nb_apple}$
 $+ 26 \times \text{nb_pear} + \dots) \wedge \dots$
- ▶ $x = (x_1, x_2, \dots, x_n) \in \mathcal{U}, x_k \in \mathbb{R}_+ \text{ or } x_k \in \mathbb{N}$
- ▶ $\dot{+} = \dot{+}^d$ with $d(x, y) = \sum_k w_k \cdot |y_k - x_k|$

Example 3: adaptation of quantities (2/2)

- For some sets of weights:

$$\text{tgt} \wedge \text{sol}(\text{tgt}) = \text{DK} \wedge (\text{nb}_{\text{apple}} = 0) \\ \wedge \boxed{(\text{nb}_{\text{pear}} = 9) \wedge (\text{mass}_{\text{sugar}} = 24)}$$

- Algorithm: transformation of the problem into a linear programming problem

Example 4: adaptation of preparations

Example 4: adaptation of preparations

- ▶ Representation of recipes using a temporal qualitative algebra

Example 4: adaptation of preparations

- ▶ Representation of recipes using a temporal qualitative algebra
- ▶ Using a revision operator on qualitative constraint networks

Conclusion and Future Work

Conclusion Belief revision offers a useful framework (or a viewpoint) for specifying adaptation in CBR

Conclusion and Future Work

Conclusion Belief revision offers a useful framework (or a viewpoint) for specifying adaptation in CBR

Future work

Conclusion and Future Work

Conclusion Belief revision offers a useful framework (or a viewpoint) for specifying adaptation in CBR

Future work

- ▶ What part of the adaptation processes does it cover?

Conclusion and Future Work

Conclusion Belief revision offers a useful framework (or a viewpoint) for specifying adaptation in CBR

Future work

- ▶ What part of the adaptation processes does it cover?
- ▶ What revision operator choosing?
(adaptation knowledge acquisition issue)

Conclusion and Future Work

Conclusion Belief revision offers a useful framework (or a viewpoint) for specifying adaptation in CBR

Future work

- ▶ What part of the adaptation processes does it cover?
- ▶ What revision operator choosing?
(adaptation knowledge acquisition issue)

There is other work not mentioned there
(but mentioned in the paper)