

Sobol' Sequences with Guaranteed-Quality 2D Projections

Supplementary Materials: Rendering results

NICOLAS BONNEEL, CNRS, Université Claude Bernard Lyon 1, INSA Lyon, France

DAVID COEURJOLLY, CNRS, Université Claude Bernard Lyon 1, INSA Lyon, France

JEAN-CLAUDE IEHL, Université Claude Bernard Lyon 1, CNRS, INSA Lyon, France

VICTOR OSTROMOUKHOV, Université Claude Bernard Lyon 1, CNRS, INSA Lyon, France

ACM Reference Format:

Nicolas Bonneel, David Coeurjolly, Jean-Claude Iehl, and Victor Ostromoukhov. 2025. Sobol' Sequences with Guaranteed-Quality 2D Projections Supplementary Materials: Rendering results. *ACM Trans. Graph.* 44, 4 (August 2025), 4 pages. <https://doi.org/10.1145/3730821>

1 Rendering results

Figures 1, 2 and 3 provide rendered images for small per-pixel sample counts (4 to 256). MSE convergence graphs are presented in the main document. First, the Cornell-box scene presents path traced results with direct lighting and 1 bounce of indirect lighting thus requiring $5 + 6 + 6$ dimensions: 5 dimensions are used to sample pixel, lens and time, 3 dimensions then sample the direct lighting and 3 more dimensions are sampled to find the next vertex of the path. Extending the path one more time requires another 6 dimensions. The Spaceship scene samples longer refractive paths thus requiring 4 indirect bounces, resulting in a total of 35 dimensions. The last scene, the Dining-Room, is lit both directly and indirectly, we use simple 2 bounces paths and 17 dimensions.

The authors acknowledge Benedikt Bitterli [Bitterli 2016] for providing those high quality scene descriptions.

References

- Benedikt Bitterli. 2016. Rendering resources. <https://benedikt-bitterli.me/resources/>.
- Brent Burley. 2020. Practical hash-based Owen scrambling. *Journal of Computer Graphics Techniques (JCGT)* 10, 4 (2020), 29.
- Henri Faure and Christiane Lemieux. 2016. Irreducible Sobol' sequences in prime power bases. *Acta Arithmetica* 173, 1 (2016), 59–80.
- Stephen Joe and Frances Y Kuo. 2008. Constructing Sobol sequences with better two-dimensional projections. *SIAM Journal on Scientific Computing* 30, 5 (2008), 2635–2654.
- Victor Ostromoukhov, Nicolas Bonneel, David Coeurjolly, and Jean-Claude Iehl. 2024. Quad-optimized low-discrepancy sequences. In *Proceedings of ACM SIGGRAPH*.
- Loïs Paulin, David Coeurjolly, Jean-Claude Iehl, Nicolas Bonneel, Alexander Keller, and Victor Ostromoukhov. 2021. Cascaded Sobol'Sampling. *ACM Transactions on Graphics (TOG)* 40, 6 (2021), 1–13.
- Matt Pharr, Wenzel Jakob, and Greg Humphreys. 2023. *Physically based rendering: From theory to implementation* (4th ed.). MIT Press.

Authors' Contact Information: Nicolas Bonneel, CNRS, Université Claude Bernard Lyon 1, INSA Lyon, France, nicolas.bonneel@liris.cnrs.fr; David Coeurjolly, CNRS, Université Claude Bernard Lyon 1, INSA Lyon, France, david.coeurjolly@cnrs.fr; Jean-Claude Iehl, Université Claude Bernard Lyon 1, CNRS, INSA Lyon, France, jean-claude.iehl@liris.cnrs.fr; Victor Ostromoukhov, Université Claude Bernard Lyon 1, CNRS, INSA Lyon, France, victor.ostromoukhov@liris.cnrs.fr.



This work is licensed under a Creative Commons Attribution 4.0 International License.

© 2025 Copyright held by the owner/author(s).

ACM 1557-7368/2025/8-ART

<https://doi.org/10.1145/3730821>




Fig. 1. Rendering 2 bounces indirect lighting in 17D. We compare our results with the ones obtained from White Noise (a), Sobol' with Joe and Kuo [2008] (b), Faure and Lemieux [2016] (c), Quad Optimized in GF(3) [Ostromoukhov et al. 2024] (d), Cascaded Sobol' [Paulin et al. 2021] (e), ZeroTwo [Pharr et al. 2023] (f) and Padded Sobol' 4D [Burley 2020] (g).



Fig. 2. Rendering 5 bounces indirect lighting in 35D. We compare our results with the ones obtained from White Noise (a), Sobol' with Joe and Kuo [2008] (b), Faure and Lemieux [2016] (c), Quad Optimized in GF(3) [Ostromoukhov et al. 2024] (d), Cascaded Sobol' [Paulin et al. 2021] (e), ZeroTwo [Pharr et al. 2023] (f) and Padded Sobol' 4D [Burley 2020] (g).



Fig. 3. Rendering 2 bounces indirect lighting in 17D. We compare our results with the ones obtained from White Noise (a), Sobol' with Joe and Kuo [2008] (b), Faure and Lemieux [2016] (c), Quad Optimized in GF(3) [Ostromoukhov et al. 2024] (d), Cascaded Sobol' [Paulin et al. 2021] (e), ZeroTwo [Pharr et al. 2023] (f) and Padded Sobol' 4D [Burley 2020] (g).